CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION OFFICE OF THE STATE FIRE MARSHAL FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM

LISTING SERVICE

LISTING No. 7135-0067:210 Page 1 of 2

CATEGORY: Audible Signal Devices

LISTEE: Siemens Building Technologies Inc., *Fire Safety Div., 8 Fernwood Rd, Florham Park NJ 07932

Contact: Peter Pawchak (973) 593-2662 Fax (973) 593-6652

DESIGN: Models U-MHST, -1G, -1G-W, -W; U-MH, -1G, -1G-W, -W; U-MHT, -1G, -1G-W, -W; U-MHT

MMT, -1G, -1G-W, -W electronic horns.

Models U-MH-S17, U-MH-S17S, U-MH-S30, U-MH-S30S, U-MH-S60, U-MH-S60S, U-MH-S75, U-MH-S75S, U-MH-S110, U-MH-S110S with or without suffix -C, -W, -W-C electronic

horn/strobes. Models U-MH-MCS, U-MH-MCS-W multi-candela synchronizable

horn/strobe.

Models U-MHT-S17, U-MHT-S17S, U-MHT-S30, U-MHT-S30S, U-MHT-S60, U-MHT-S60S, U-MHT-S75, U-MHT-S75S, U-MHT-S110, U-MHT-S110S with or without suffix -C, -W, -W-C

electronic horn/strobes. Models U-MHT-MCS, U-MHT-MCS-W multi-candela

synchronizable horn/strobe.

Models U-MMT-S17, U-MMT-S17S, U-MMT-S30, U-MMT-S30S, U-MMT-S60, U-MMT-S60S, U-MMT-S75S, U-MMT-S110, U-MMT-S110S with or without suffix -C, -W, -W-C electronic horn/strobes. Models U-MMT-MCS, U-MMT-MCS-W multi-candela

synchronizable horn/stobe.

 $\label{eq:models-u-mhst-s17S} Models \ U-MHST-S17S, \ U-MHST-S30S, \ U-MHST-S60S, \ U-MHST-S75S, \ U-MHST-S110S \\ with or without suffix -C, -W, -W-C electronic horn/strobes. \ Models \ U-MHST-MCS, \ U-MHST-MCS$

MHST-MCS-W multi-candela synchronizable horn/stobe.

Model U-MMT Series horn and U-MMT Series horn/strobes are multi-tone devices. All synchronized devices must be used with Models SCM-F, SCM-FW, DSC, DSC-W sync module. Refer to listee's data sheet for additional detailed product description and

operational considerations.

RATING: Electrical: 20 - 31 VDC

Candela: 15/75 cd, 30/75 cd, 60/75 cd, 75 cd, 110 cd

Flash Rate: 60 Flashes/Minute

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes & ordinances

and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee's name or Cerberus Pyrotronics, model number, electrical, candela, audibility rating,

and UL label.

*Rev. 10-26-2002

APPROVAL:

Listed as horns and horn/strobes for use with separately listed compatible fire alarm control units. For indoor use only

units. For indoor use only.

Models U-MH series cannot produce a distinctive three-pulse Temporal Pattern Fire Alarm Evacuation Signal (for total evacuation) in accordance with NFPA 72, 1996 Edition. If required, Series U-MH must be used with a fire alarm control unit that can generate the temporal pattern signal. All other models can generate the temporal-three code pattern. Refer to manufacturer's Installation Manual for details.

XLF: 7135-0065:145

*Rev. 10-26-2002



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.

Date Issued: OCTOBER 26, 2002 Listing Expires June 30, 2003

Authorized By: **DIANE K. AREND**, Senior Deputy

Program Manager